



POLYPROPYLENE CONDUIT

**HALOGEN
FREE
LOW SMOKE
NFR
NON FLAME
RETARDANT
PROTECTIVE
INSULATING
CORRUGATED
PLIABLE CONDUITS
SYSTEM**

THIS PRODUCT CAN ALSO BE SUPPLIED ON A SPLIT VERSION ADD "SPLIT" AFTER CODE. Please note this will change the IP rating.

THIS PRODUCT CAN ALSO BE SUPPLIED WITH A DRAW WIRE PLEASE ADD "DW" AFTER CODE

APPLICATIONS	DATA INSTALLATIONS
MATERIAL	POLYPROPYLENE
STANDARDS	EN50086.1 EN50086.22 Superseded by EN61386.1 and EN61386.22
COLOUR	BLACK/WHITE standard. RED, YELLOW, ORANGE, GREY & BLUE also available MOQ may apply.
COMPRESSION RESISTANCE	Class 2 = Light 320N on 5cm at 20° C
IMPACT RESISTANCE	Class 2 = Light 1 Joule at 5° C
MINIMUM TEMPERATURE INSTALLATION AND APPLICATION RANGE -5° C MAXIMUM TEMPERATURE INSTALLATION AND APPLICATION RANGE +90° C	

PART No:	TRADE SIZE	OD mm	ID mm	COIL M
CO7	7	7	4.5	50
CO10	10	10	6.9	50
CO12	12	12	10	50
CO16	16	16	10.7	100
CO20	20	20	14.1	100
CO25	25	25	18.2	50/100
CO32	32	32	24.2	50
CO40	40	40	32.4	25
CO50	50	50	41.2	25
CO63	63	63	54	25



Please note: The information given is provided on the basis that errors, omissions and amendments are excepted. As part of the programme of on-going product development, reserves the right to change product specifications without prior notice. All information provided is correct at the time of first publication, whether in digital or print form. Third party approvals where indicated may apply only to certain product sizes, please check with us for clarification. Application information and product data is provided for guidance only and does not constitute a warranty of any kind whether expressed or implied in respect of products or their suitability for a particular purpose.