

W31 Indoor/Outdoor Lockable Wall Box - 24 Fibers - SC Adaptors



Description

This Lockable IP65 distribution box is supplied loaded or unloaded and offers the ability to terminate 24 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 24 SC simplex connections and splices. The box has 24 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in un-secure areas.

Features and Benefits

- IP 65 Rating for external use
- Integrated cable tie points for securing incoming cable
- Removable splice tray for easy installation
- Integrated bend radius protection
- Cable entry point allows unbroken cable to be installed(loop)
- Supplied with 24 heatshrink splice protectors
- Supplied with wall fixings and tie wraps
- Lockable door for added security
- Up to 24 splice & SC connection points
- Accepts loose tube, distribution and pre-terminated cables
- Sealing glands for up to 24 exiting cables + 2 incoming cable
- Removable door for ease of installation
- Supplied with transit tubing
- ROHS, REACH & SvHC compliant

ELEMENT	CHARACTERISTIC
Height (mm)	340
Width (mm)	270
Depth (mm)	110
Net weight (kg)	1.8
Suitable for adapter type	SC Simplex
Number of ports	24
Cable entry	2
Material	ABS
Colour	Grey RAL 7035
	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,
Compliant to	RoHS, Reach/SVHC