



55-65 Castleham Road, St Leonards on Sea

East Sussex, TN38 9NU

Customer Services: +44 (0) 1424 856600


T: +44 (0) 1424 856655 F: +44 (0) 1424 856611

E: sales@marshall-tufflex.com

www.marshall-tufflex.com

Conduit (Heavy Gauge) Product Data Sheet

Product Pange	CR6, CR7 & CR8
Product Range	CRO, CRY & CRO
Description	PVCu Round Conduit
Key Features	Heavy Gauge Range of Inspection Elbows, Bends & Tees Range of fittings Range of Round & Square boxes Operating Temperature -5°C to +60°C Non-Flame Propagating to BS EN 61386-1 High Impact Resistance to -5°C Heavy Gauge Requirements of BS EN 61386-1
Dimensions	20mm, 25mm & 32mm
Material(s)	PVCu (White and Black)
Compliance / Standards(s)	CE & UKCA Marked
	Low Voltage Directive 2014/35/EU
	The Electrical Equipment (Safety) Regulations 2016
	BS 7671:2018
	BS EN 61386-1:2008+A1:2019
	BS EN 60386-21:2004+A11;2010
	BS 4607-1:1984+A2:2010
	BS 4607-5:1982+A3:2010
Packaging	Recyclable



We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our PVC-U products are manufactured from an average of 80% recycled plastic, with some extruded products produced from 100% recycled material.



Conduit is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

To find out more about the percentage of recycled material used in this product, please visit marshall-tufflex.com

DOC00302 Issue 6














Page 1 of 1