Server Lifts



The Genie® GL™ Server Lift range consists of standard or counterweight models designed to make the movement and handling of IT equipment easier.

Standard Base

The Standard Base Genie® GL™ Server Lift has a compact design and low loading height that allows you to lift and manoeuvre in tight spaces. Available in GL-4 and GL-8 models.

Counterweight Base

The Counterweight Base Genie® GL™ Server Lift has a short leg length that enables you to work closer to the carried load. Available in GL-4, GL-8 and GL-10 models.



- Portable and compact design.
- Lightweight durable, telescoping aluminium construction.
- Removing platform exposes durable steel forks that provides extra versatility for lift.
- Standard lift has 20cm non-marking rear wheels and 5cm dual wheel front swivel castors.
- Counterweight lift has 12.7cm rear swivel castors with side brakes and 10cm fixed front wheels.
- Loads are lifted or lowered using standard winch.



GL™-4

- 1.30m Maximum lift height.
- Up to 227Kg load capacity.

GL™-8

- 2.5m Maximum lift height.
- Up to 181Kg load capacity.

GL™-10


- 3.01m Maximum lift height.
- Up to 159Kg load capacity.



Standard GL™ Lift with Platform



Counterweight GL™ Lift with Platform



Specifications

	GL™-4	GL™-8	GL™-10
Measurements			
A - Height - Maximum Forks Down	1.30m	2.50m	3.01m
Standard Base			
B - Length - Operating	88cm	88cm	-
C - Width - Outside	63cm	63cm	-
Weight With Standard Castors	51Kg	60Kg	-
Counterweight Base			
Length - Operating	1.10m	1.10m	1.10m
Width - Maximum	75cm	75cm	75cm
Weight With Standard Castors	178Kg	186Kg	196Kg
Productivity			
Load Height Minimum	9cm	9cm	9cm
Average Cranks With Standard Winch	38/m	38/m	38/m
Fork Length	57cm	57cm	57cm
Fork Width	52cm	52cm	52cm
Load Platform Length	58cm	58cm	58cm
Load Platform Width	56cm	56cm	56cm
Load Capacity	227Kg	181Kg	159Kg
Part Numbers			
Standard Base With Load Platform	GL-4-S	GL-8-S	-
Counterweight Base With Load Platform	GL-4-C	GL-8-C	GL-10-C



Load platform fits over forks and insures equipment is transported safely.



Counterweight Lift has short front legs and rear castors fitted with side brakes.